



DT Swiss 350 Straightpull XM421 29" 1670g 5x100 QR / 12x142 TA Shimano MTB wheels

Availability

 **Unavailable**

Number

90010777

EAN

1016488067038

Product description

TECHNICAL DATA

Element:
RIMS

Description:
DT Swiss XM 421

25mm 28H

Notes:

A rim that is lightweight and yet as wide as those of a few years ago? State-of-the-art materials and numerous tests make it possible. DT Swiss knows exactly how to design a lightweight product that is meant to accomplish its goal. That's why the **XM 421** is as light as a mountain outline while still being unafraid of terrain no matter what rocky trails are on the menu.

Tubeless Compatible - These rims can be converted for tubeless tires using the Tubeless

SBWT welded kit- two special inserts, pressed at both ends, ensure that the rim profile is stabilized at the welding stage. The final correction of the weld is done on the machining center.

XM (Cross Mountain) - a group of components for riders who want to do everything. Climbing the Alps, a weekend on the bike with a group of friends or participating in a bike marathon - versatility and reliability are as important as weight and comfort.

5x100 QR / 5x130 QR Shimano 11s Road

BEHIND SPRINGS

Front:
DT Swiss 350 straightpull MTB Disc Brake

Rear:
DT Swiss 350 straightpull MTB Disc Brake
Disc Brake
Dt Swiss competition race 2.0/1.8/2.0

WHEELS DESIGNED FOR BRAKES: SPRINGS

disc mount IS / 6 bolts

NYPLE

Sapim SILS sLock polyax aluminum

Sapim SILS sLock polyax aluminum

Lightweight Polyax aluminum nipples. Weight 10.8 g (36 pcs). Made of very strong EN 7075 aluminum. coated with a special coating to reduce friction and increase corrosion resistance.

Coating - Special coating is a new way to reduce friction on aluminum nipples. The coating is applied to the thread and the nipple. This reduces friction on the spoke-nipple, rim-nipple line. The coating also increases corrosion resistance.

Polyax - Polyax nipples are patented by Sapim. Thanks to their special design, they help the nipple fit the rim. This solves the problem of the spoke kinking in the nipple. This allows the spokes to fit better in the wheel.

SILS - (Sapim Integrated Locking System) system which prevents the nipple from loosening. SILS, causes self-locking on the nipple and does not loosen/unloosen over time, allowing the wheels to be properly tensioned at all times. the locking system, however, allows you to adjust the tension of individual spokes when needed.

stated weight may vary slightly due to possible uniqueness of weight of individual components

stated weight may vary slightly due to possible uniqueness in weight of individual components

weight shown may vary slightly due to possible uniqueness in weight of individual components

If you do not meet the weight criteria please contact the staff - we will help you select components that will meet the strength criteria for the user's weight.

WEIGHT: FRONT WHEEL weight stated without clamp	775g
WEIGHT: REAR WHEEL weight given without clamp	905g
WEIGHT: KIT weight shown without clamp	1670g
WHEEL CLAMPS weight, model	no
Number of spokes front / rear	28H / 28H
Compatibility with TL-Rea system	Yes
RECOMMENDED WEIGHT OF THE USER :	Up to 110kg
PURPOSE	All Mountain
WARRANTY TIME	24 months